PRINT 3DD

บริษัท เมดิคัลเทค จำกัด / บริษัท นิโอเทค จำกัด
www.print3dd.com






Kings


Kings 600 Pro

Leading Brand in Industrial SLA 3D Printer

Build Size: XYZ 600mm×600mm×400mm
Equipment Size: 108cm×120cm×198cm
Equipment Weight:about 980kg
Rated Dissipation: 1.5KVA
Resin Tank Weight: about 240kg














Industrial SLA SLS SLM

3D Printer ระดับอุตสาหกรรม เพื่อการผลิต

ตอบสนองความต้องการงาน 3D ทุกรูปแบบ ไม่ว่าจะเป็นงาน resin, polymer, metal



Kings SLA 6035Pro ระบบเรซิ่น

Build Size: 350mm×600mm×350mm
Equipment Size: 108cm×95cm×198cm
Equipment Weight: about 880kg
Rated Dissipation: 1.5KVA
Resin Tank Weight: about 160kg



Kings SLA 800Pro ระบบเรซิ่น

Build Size: 800mm×800mm×500mm
Equipment Size: 129cm×139cm×220cm
Equipment Weight: about 1200kg
Rated Dissipation: 1.8KVA
Resin Tank Weight: about 500kg



Kings SLA 1700 Pro ระบบเรซิ่น

Build Size: 1700mm×800mm×600mm
Equipment Size: 239cm×159cm×226cm
Equipment Weight: about 2400kg
Rated Dissipation: 1.8KVA
Resin Tank Weight: about 1300kg



EP-C series Wax/Sand SLS printer ระบบ SLS

Material: PS, resin sand, TPU, etc.
Build Volume: 700 x 700 x 500 mm
Layer Thickness: 0.15 mm (0.04-0.3 mm to choose)
Build Accuracy: 0.15mm (part size100mm), 0.15% (part size 100mm)
Material Feed ModeAutomatic loading, Bi-directional powder feeding
Laser Power CO2 laser, 100 w



EP-P380 SLS Nylon Printer ระบบ SLS

Material: PA12 , PA12GF , PP , TPU , PE , TPE
Build Volume 380 x 380 x 500 mm
Layer Thickness: 0.1 mm (0.04-0.3 mm to choose)
Build Accuracy: ±0.15mm (part size 100mm), ±0.15% (part size 100mm)
Material Feed Mode: Automatic loading, bi-directional powder feeding
Laser Power: CO2 laser, 55 w



EP-M100T Direct Metal Printer เครื่องพิมพ์โลหะ

Material:
Stainless steel, maraging steel, high temperature nickel base alloy, cobalt chromium alloy, high strength steel, copper alloy
Building Volume 120 × 120 × 80 mm
Layer Thickness 0.015-0.05 mm
Laser Power 100 w/200 w



EP-M250 Direct Metal Printer เครื่องพิมพ์โลหะ

Material: Stainless steel, maraging steel, nickel base alloy, titanium alloy, cobalt chromium alloy, aluminum alloy, copper alloy
Building Volume 250 x 250 x 300 mm
Layer Thickness 0.02 - 0.1 mm
Laser Power 200 w or 500 w